

CHIPS SPREADER

our electric chip spreader, based on European, is installed as a replacement of the rear side board of tipping lorries, by hinges (loose supply) to be welded on the back part of the truck.

it is Provided with:

- Mechanical roller functioning by geared motor connected to the truck battery's 24 V supply spreading the gravel, with start / stop control taken into the cabin.
- Chute with spokes, for spreading the gravel.

TECHNICAL DATA

Overall length	2580 mm
Overall width	1380 mm
Overall height	1260 mm
Roller dia	194 mm
DC electric motor	0.46 HP, 24 V

PRODUCT #	DESCRIPTION	WEIGHT
E2330	10' spread width, 1.41 cu. yd. capacity	2,420 lbs.
Optional Features:		
PE2380	10' Operator Platform	
PE2460	Truck Hitch - 1 supplied with each spreader	
PE2470	12" Block-Off Plates - to alter width of spread	
PE2480	24" Block-Off Plates - to alter width of spread	
PE2490	Tailgate Hook - (2 required) Two tailgate hooks supplied with each spreader	
E2500	R-1 Trailer System - For towing aggregate spreader	
E9000	Blocking / Bracing Charge (if required)	400 lbs.



➤ Contact Us

Aaspa Equipment Pvt.Ltd

📍 A-112, Sahjanand Business Park, Opp Palm Hotel, Odhav, Ahmedabad, -382415

☎ +91 9898341024 +91 9428325161

✉ info@aspaequipment.com, sales@aspaequipment.com

🌐 www.aspaequipment.com